

## Betonrohre KF-F (Falz) DIN 4032

Artikel-Nr.	Lichte Weite mm	Baulänge mm	Gewicht kg	Wandstärke mm
10120	150	1000	40	30
10121	200	1000	58	30
10122	300	1000	120	45
10123	400	1000	175	45
10124	500	1000	275	60
10125	600	1000	360	60
10126	800	1000	600	95
10127	1000	1000	1000	110



## Betonrohre KF-F (Falz) gelocht

Artikel-Nr.	Lichte Weite mm	Baulänge mm	Gewicht kg	Wandstärke mm
10130	150	1000	40	30
10131	200	1000	56	30
10132	300	1000	120	45



## Betonschwerlastrohre KF-W mit Falz wandverstärkt

Artikel-Nr.	Lichte Weite mm	Baulänge mm	Gewicht kg	Wandstärke mm
10135	300	1000 wandv.	190	50
10136	400	1000 wandv.	275	60
10137	500	1000 wandv.	400	70
10138	600	1000 wandv.	560	90
10139	800	1000 Atlas	950	90
10140	1000	1000 Atlas	1450	105



## Betonrohr - Böschungsköpfe

Artikel-Nr.	Lichte Weite mm	Gewicht kg
10143	300	80
10144	400	200
10145	500	270
10146	600	370
10147	800	900
10148	1000	1680

